

Knurling tools holders and knurling wheels

Type: DVR, VK

1.	Is it possible to use holders DVR20 on CNC machines?	If the rose is ensured against place change by its rotation.
2.	What knurling wheels can be used to holders?	Knurling wheels with the biggest outer diameter 20mm, slot 6mm and width 10mm. According to quality it can be wheels with milled or stamped profile or it can be more qualit version with grinded profile.
3.	Some wheels with slant profile have obliquing 45° and some 30°. Why?	Most of suppliers deliver angel 30°, now we do not deliver other wheels.
4.	Is it possible to deliver holders DVR20 with other profile of bearing body?	For demand.
5.	Is it possible to deliver holders DVR20 with wheels in set?	It is possible, but you must specify your requirement in order.
6.	Is it possible to order wheels produced form material HSS?	It is possible but they will be grinded.
7.	What is difference between milled wheel and stamped wheel?	There is almost no difference for user because edge has the same quality. It is not so sharp like on grinded profile wheel. The sharper is edge the lower thrust is necessary to its kerf.

NAREX MTE s.r.o., Moskevská 63, CZ-101 00 Prague 10, Czech Republic

e-mail: sales@narexmte.cz

<http://www.narexmte.cz/>

Phone: +420 246 002 249, +420 246 002 321

Fax: +420 246 002 335, +420 246 002 343

